



Marshall Best Security Corporation



- 16 – Deadlock by key on either side
- 17 – Deadlock by key O/S and Turnknob I/S
- 18 – Deadlock by key one side only

Available Functions

US3 (605)	US4 (606)	US10B (613)
US26 (625)	US26D (626)	

Available Finishes

	ANSI Strike	Thumb Turn

HOW TO ORDER

<u>Model</u>	<u>Function</u>	<u>Finish</u>
MBS-DBM	16	630
MBS-DBM	See Function Chart	See Finish Chart

DBM

Heavy Duty Auxiliary Mortise Deadbolt locks

Specifications:

Applications

To use as an auxiliary lock for quality residential and commercial buildings wherever additional security is desired.

Door Ranges

1 3/8" to 2" door thickness.

Backset

2 3/4" standard.

Bolt

1" throw, stainless steel deadbolt, Anti-Saw deadbolts with hardened pins.

Handing

Non-Handed.

Cylinder

Accepts standard Mortise Cylinders. **Cylinder and I/C Core not included.**

Certifications

Meets or exceeds ANSI A156.5 Grade 1 strength and operational requirements.

Code Compliance



ADA Barrier-Free Accessibility

Marshall Best Security Corporation
13097 Parkside Drive
Fishers, IN 46038

Phone: 317-806-1180
Fax: 317-578-2904